

**PENDING CLAIMS AS AMENDED**

Please amend the claims as follows:

1. (Original) A method for time synchronizing a second base station with a first base station comprising:
  - measuring a round trip delay interval of transmissions from the first base station to a mobile station in communication with the first base station and back from the mobile station to the first base station;
  - receiving at the second base station communications transmitted by the mobile station and noting the time of reception;
  - determining an estimate of a delay which occurs between transmission by the mobile station and reception by the second base station; and
  - computing a timing correction value in accordance with said estimate of the delay, said noted time of reception, and said measured round trip delay interval.
2. (Original) The method of claim 1 further comprising receiving at the second base station a message indicative of the identity of the mobile station to assist the second base station in said receiving communications from the mobile station.
3. (Original) The method of claim 2 further comprising sending the message indicative of the identity of the mobile station from the first base station to the second base station.
4. (Original) The method of claim 3 wherein said sending the message from the first base station to the second base station comprises:
  - sending the message from the first base station to the second base station via a base station controller in communication with the first base station and the second base station.

Attorney Docket No.: QCPA453B1C1  
Customer No.: 236962

5. (Original) The method of claim 3 wherein said sending the message from the first base station to the second base station comprises:

receiving at the first base station communications from a plurality of mobile stations;  
selecting a mobile station most likely to be able to communicate with the second base station; and  
sending the message indicative of the identity of the mobile station.

6. (Original) The method of Claim 5 wherein said selecting a mobile station most likely to be able to communicate with the second base station comprises:

selecting a mobile station furthest from the first base station.

7. (Original) The method of Claim 5 wherein said selecting a mobile station most likely to be able to communicate with the second base station comprises:

selecting a mobile station closest from the first base station.

8. (Original) The method of Claim 5 wherein said selecting a mobile station most likely to be able to communicate with the second base station comprises:

selecting a mobile station in accordance with the state of a PN spreader in the mobile station.

9. (Original) The method of claim 5 wherein said selecting a mobile station most likely to be able to communicate with the second base station comprises:

selecting a mobile station in accordance with the sector of the first base station being used for communication with the mobile station.

10. (Original) The method of claim 5 wherein said selecting a mobile station most likely to be able to communicate with the second base station comprises:

selecting a mobile station in accordance with said measured round trip delay interval.

11. (Original) An apparatus for time synchronizing a second base station with a first base station comprising:

a first base station configured to:

measure a round trip delay interval of transmissions from said first base station to a mobile station in communication with said first base station and back from the mobile station to said first base station; and

a second base station configured to:

receive communications transmitted by the mobile station and noting the time of reception;

determine an estimate of a delay which occurs between transmission by the mobile station and reception by said second base station; and

compute a timing correction value based upon the estimate of the delay, the time of reception, and the measured round trip delay interval.

12. (Original) The apparatus of claim 11 wherein said second base station is further configured to receive a message indicative of the identity of the mobile station to assist said second base station to receive communications from the mobile station.

13. (Original) The apparatus of claim 12 wherein said first base station is further configured to send the message indicative of the identity of the mobile station to said second base station.

14. (Original) The apparatus of claim 13 wherein said first base station is further configured to send the message to said second base station via a base station controller in communication with said first base station and said second base station.

15. (Original) The apparatus of claim 13 wherein said first base station is further configured to:

receive communications from a plurality of mobile stations; and

select a mobile station most likely to be able to communicate with said second base station.

16. (Original) The apparatus of Claim 15 wherein said first base station is configured to select the mobile station most likely to be able to communicate with said second base station as a mobile station furthest from said first base station.

17. (Original) The apparatus of Claim 15 wherein said first base station is configured to select the mobile station most likely to be able to communicate with said second base station as a mobile station closest from said first base station.

18. (Original) The apparatus of Claim 15 wherein said first base station is configured to select the mobile station most likely to be able to communicate with said second base station in accordance with the state of a PN spreader in the mobile station.

19. (Original) The apparatus of claim 15 wherein said first base station is configured to select the mobile station most likely to be able to communicate with said second base station in accordance with the sector of said first base station being used for communication with the mobile station.

20. (Original) The apparatus of claim 15 wherein said first base station is configured to select the mobile station most likely to be able to communicate with said second base station in accordance with said measured round trip delay interval.

Claims 21-30. (Canceled)

31. (Currently Amended) ~~The method of claim 27 wherein said estimating at the base station distance to the mobile station comprises:~~ A method for synchronizing a base station with a wireless communication system upon the base station's power up, comprising:  
disabling a transmission from the base station;

Attorney Docket No.: QCPA453B1C1  
Customer No.: 236965

obtaining initial timing at the base station;

receiving at the base station signals transmitted from a mobile station, including:

(i) providing to the base station information about identify of the mobile station;

(ii) estimating at the base station distance to the mobile station in accordance with a first round trip delay interval of transmissions from a first base station to the mobile station in communication with the first base station and back from the mobile station to the first base station, and a second round trip delay interval of transmissions from a second base station to the mobile station in communication with the second base station and back from the mobile station to the second base station[.]; and

(iii) receiving at the base station signals transmitted from the mobile station in accordance with the provide information and the estimated distance;  
and

adjusting timing of the base station in accordance with the received signals.

32. (Currently Amended) ~~The method of claim 26 wherein adjusting timing of the base station in accordance with said received signals comprises:~~ A method for synchronizing a base station with a wireless communication system upon the base station's power up, comprising:

disabling a transmission from the base station;

obtaining initial timing at the base station in accordance with a timing signal provided from a base station controller;

receiving at the base station signals transmitted from a mobile station; and

adjusting timing of the base station in accordance with a time offset between an estimated PN offset of the mobile station and an actual PN offset of the mobile station.

Claim 33. (Canceled)

34. (Currently Amended) ~~The method of claim 33 wherein said providing the mobile station with an identity of the base station comprises:~~ A method for synchronizing a base station with a wireless communication system upon the base station's power up, comprising:

disabling a transmission from the base station;

obtaining initial timing at the base station in accordance with a timing signal provided from a base station controller;

receiving at the base station signals transmitted from a mobile station;

adjusting timing of the base station in accordance with the received signals;

providing the mobile station with an identity a pilot PN code offset of the base station;  
and

transmitting signals at successively increasing power levels from the base station in accordance with the adjusted timing until the mobile station detects the transmitted signals.

35. (Currently Amended) The method of claim 33 34 wherein said the providing the mobile station with an identity of the base station comprises:

providing the mobile station with a pilot PN code.

36. (Currently Amended) The method of claim 33 34 further comprising:

synchronizing timing of the base station with at least one base station communicating with the mobile station.

37. (Original) The method of claim 36 wherein said synchronizing timing of the base station with at least one base station communicating with the mobile station comprises:

initiating a communication between the base station and the mobile station;

measuring a first round trip delay interval of transmissions from the base station to the mobile station in communication with the base station and back from the mobile station to the base station;

Attorney Docket No.: QCPA453B1C1  
Customer No.: 236967

measuring a second round trip delay interval of transmissions from the at least one base station communicating with the mobile station and back from the mobile station to the at least one base station communicating with the mobile station;

measuring at the mobile station a time difference between the time of receipt of a transmission from the at least one base station communicating with the mobile station and the time of receipt of a transmission from the base station communicating with the mobile station; and

computing a timing correction value based upon, said measured first round trip delay interval, said measured second round trip delay interval, and said measured time difference.

38. (Original) The method of claim 36 further comprising:

repeating said synchronizing timing of the base station with at least one base station communicating with the mobile station for all mobile stations within the coverage area of the base station.

39. (Original) The method of claim 36 wherein synchronizing timing of the base station with at least one base station communicating with the mobile station comprises the method as claimed in claim 1.

Claims 40-49. (Canceled)

50. (Currently Amended) ~~The apparatus of claim 46 wherein said processor estimates a distance from the base station to the mobile station by executing a set of instructions to:~~ An apparatus for synchronizing a base station with a wireless communication system upon the base station's power up, comprising:

a transmitter;

a processor communicatively coupled to the transmitter, the processor being configured to execute a set of instructions to adjust timing of the base station in accordance with the received signals, obtain information about identity of a mobile station, and estimate a distance from the base station to the mobile station by estimate estimating a first round trip

Attorney Docket No.: QCPA453B1C1  
Customer No.: 236968

delay interval of transmissions from a first base station to the mobile station in communication with the first base station and back from the mobile station to the first base station[[:]], and estimate estimating a second round trip delay interval of transmission from a second base station to the mobile station in communication with the second base station and back from the mobile station to the second base station;

a storage medium coupled to the processor and containing another set of instructions executable by the processor to disable the transmitter and obtain initial timing; and

a receiver, communicatively coupled to the processor, configured to receive signals transmitted from the mobile station, adjust timing of the base station in accordance with the received signals, and receive signals transmitted from the mobile station in accordance with the provide information and the estimated distance.

51. (Currently amended) ~~The apparatus of claim 46 wherein said processor estimates a distance from the base station to the mobile station by executing a set of instructions to:~~ An apparatus for synchronizing a base station with a wireless communication system upon the base station's power up, comprising:

a transmitter;

a processor communicatively coupled to the transmitter, the processor being configured to execute a set of instructions to adjust timing of the base station in accordance with a time offset between an estimated PN offset of the mobile station and an actual PN offset of the mobile station;

a receiver, communicatively coupled to the processor, configured to receive signals transmitted from the mobile station; and

a storage medium coupled to the processor and containing another set of instructions executable by the processor to disable the transmitter and obtain initial timing.

Claim 52 (Canceled)



53. (Currently Amended) ~~The apparatus of claim 52 wherein the mobile station is~~  
An apparatus for synchronizing a base station with a wireless communication system  
upon the base station's power up, comprising:

a transmitter;

a processor communicatively coupled to the transmitter, wherein the processor  
executes a set of instructions to adjust timing of the base station in accordance with received  
signals;

a receiver, communicatively coupled to the processor, configured to receive the  
received signals transmitted from a mobile station; and

a storage medium coupled to the processor and containing another set of instructions  
executable by the processor to disable the transmitter and obtain initial timing;

wherein the mobile station being configured to obtain information about a pilot PN  
code of the base station and the transmitter being configured to transmit signals at  
successively increasing power levels from the base station in accordance with the adjusted  
timing until the mobile station detects the transmitted signal.

54. (Currently Amended) The apparatus of claim 52 ~~53~~ wherein the mobile station  
is configured to obtain information about a pilot PN code of the base station.

55. (Currently Amended) ~~The apparatus of claim 45 said processor further~~  
~~executes a set of instructions~~ An apparatus for synchronizing a base station with a wireless  
communication system upon the base station's power up, comprising:

a transmitter;

a processor communicatively coupled to the transmitter, wherein the processor  
executes a set of instructions to adjust timing of the base station in accordance with received  
signals, and to synchronize timing of the base station with at least one base station  
communicating with said a mobile station;

a receiver, communicatively coupled to the processor, configured to receive the  
received signals transmitted from the mobile station; and

a storage medium coupled to the processor and containing another set of instructions executable by the processor to disable the transmitter and obtain initial timing.

56. (Currently Amended) The apparatus of claim 45 ~~55~~ wherein ~~said~~ the processor synchronizes timing of the base station with at least one base station communicating with the mobile station by executing a set of instructions to:

initiate a communication between the base station and the mobile station;

measure a first round trip delay interval of transmissions from the base station to the mobile station in communication with the base station and back from the mobile station to the base station;

measure a second round trip delay interval of transmissions from the at least one base station communicating with the mobile station and back from the mobile station to the at least one base station communicating with said mobile; and

compute a timing correction value in accordance with the first round trip delay interval, the second round trip delay interval, and a time difference provided by the mobile station; and wherein

the mobile station is configured to:

measure the time difference between the time of receipt of a transmission from the at least one base station communicating with the mobile station and the time of receipt of a transmission from the base station.

57. (Currently Amended) The apparatus of claim 54 wherein ~~said~~ the processor repeats ~~said~~ the synchronizing timing of the base station with at least one base station communicating with the mobile station for all mobile stations within the coverage area of the base station.

58. (Currently Amended) The apparatus of claim 54 ~~wherein further comprises~~ further comprising the apparatus as claimed in claim 11.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**